SAFETY DATA SHEET

NAME OF PRODUCT HH60, HG60, 4R60S, 4R60C, 4R60X

FILE NUMBER: HH60, HG60, 4R60S, 4R60C, 4R60X

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SYNONYMS: PRODUCT CODE: MANUFACTURER: ADDRESS: EMERGENCY PHONE: RECOMMENDED USE: RESTRICTIONS ON USE: PREPARED BY: HH60, HG60, 4R60S, 4R60C,4R60X DISTILLATE, PETROLEUM HH60, HG60 Four R Marketing, LLC 715 Ouachita Road 72, 71762 (870) 725-3333 Base/Process Oil NOT INTENDED TO BE USED AS A FUEL Four R Marketing, LLC

SECTION 2: HAZARDS IDENTIFICATION

OSHA Hazard: Aspiration toxicity **Signal word:** Danger



Aspiration Toxicity GHS Classification: 1 Kinematic viscosity ≤ 20.5 mm²/s @ 40°c = GHS Cat.1

Precautionary statements:

Prevention: Not Applicable

Response: If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.

Storage: Store locked up in a well ventilated place.

Disposal: Dispose of contents/container to comply with Federal, State and Local regulations covering chemical waste spills.

SECTION 3: COMPOSITION/ INFORMATION ON INGREDIENTS

CHEMICAL FAMILY:

DISTILLATE (PETROLEUM) HYDROTREATED LIGHT NAPHTHENIC

| COMPONENT(S) | % BY WEIGHT |
|--|----------------|
| Distillates, Petroleum, Hydrotreated Light Naphthenic CAS No. 64742-53-6 | >99 |
| | |

SECTION 4: FIRST AID MEASURES

EYES: Avoid contact with eyes. If contact occurs, immediately flush eyes with water for a minimum of 15 minutes. Seek medical attention immediately.

SKIN: Avoid contact with skin. If contact occurs, wash contact areas with soap and water. Remove and clean oil soaked clothing daily and wash affected area.

INGESTION: Do not induce vomiting. If ingested, seek medical attention.

INHALATION: Not expected to be a problem. However, if respiratory irritation, dizziness, nausea or unconsciousness occurs due to excessive vapor or mist exposure, seek medical attention. If operating conditions create airborne concentrations that exceed the exposure standard, the use of an approved NIOSH/OSHA respirator for organic vapors or air- supplied breathing equipment is recommended.

Important symptoms/effects, acute and delayed:

| EYES: | Eye contact may result in irritation and redness. Exposure to high concentrations of |
|-------------|--|
| | vapors may be irritating to the eyes. |
| SKIN: | Prolonged and repeated contact can defat the skin, which may result in dryness, |
| | dermatitis and cracking of the skin. |
| INGESTION: | Do not ingest. Ingestion may result in nausea or stomach discomfort. If swallowed do not |
| | induce vomiting, call a physician. |
| INHALATION: | Fumes may be unpleasant and may produce nausea. Remove the person to fresh air if |
| | respiratory discomfort occurs. |
| | |

Recommendations for immediate medical care and special treatment needed, when necessary:

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Persons with preexisting skin or respiratory disorders may have their conditions aggravated by overexposure to this material. Seek medical attention.

SECTION 5: FIREFIGHTING MEASURES

| FLAMMABLE LIMITS IN AIR, | UPPER: No data available | |
|--|--|--|
| (% BY VOLUME) | LOWER: No data available | |
| FLASH POINT: COC ºF: | 293º Minimum | |
| EXTINGUISHING MEDIA: | Foam, water fog, dry chemical, CO ² | |
| SPECIAL FIRE FIGHTING PROCEDURES: | Do not enter confined fire space without proper protective equipment | |
| | including self-contained breathing apparatus. See Hazardous | |
| | Decomposition Products. | |
| HAZARDOUS DECOMPOSITION PRODUCTS: Normal combustion forms carbon dioxide and water vapor, and ma produce oxides of sulfur and nitrogen. Incomplete combustion can produce carbon monoxide. | | |
| SECTION 6: ACCIDENTAL RELEASE MEASURES | | |

| PERSONAL PROTECTION: | Wear safety glasses, rubber gloves, Tyvek type coveralls and rubber boots. |
|------------------------------|---|
| ACCIDENTAL RELEASE MEASURES: | In case of spill, clean up using absorbent material such as earth or sand. |
| RCRA HAZARD CLASS: | This product is not a characteristic hazardous waste under RCRA. No EPA waste numbers are applicable for this product's components. |

SECTION 7: HANDLING AND STORAGE

| PERSONAL PROTECTION: | Wear safety glasses, rubber gloves, Tyvek type coveralls and rubber boots. |
|-----------------------|---|
| HANDLING AND STORAGE: | Avoid fire, sparks or open flame. Wear appropriate personal protective |
| VENTILATION: | equipment to ensure that this product does not contact the eyes or skin. Use adequate ventilation to keep the airborne concentrations of this material below the established exposure standard. |

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

| PEL- TWA (8 HOUR) | TWA (8 HOUR) | RECOMMENDED |
|--------------------------------------|--------------------------|---|
| 5 mg/m ³ (As oil mist) | 5 mg/m³ (As oil mist) | None |
| | | |
| | 5 mg/m ³ | 5 mg/m ³ 5 mg/m ³ |

RESPIRATORY PROTECTION:

EYE PROTECTION: SKIN PROTECTION:

If operating conditions create airborne concentrations that exceed the exposure standard for this product, the use of an approved NIOSH/OSHA respirator for organic vapors or air supplied breathing equipment is recommended. Wear appropriate safety glasses, goggles or full-face shield. Long sleeve cotton shirt and cotton pants are recommended. Wear appropriate gloves.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| APPEARANCE: ODOR: | Clear colored liquid Petroleum odor | |
|--|--|--|
| ODOR THRESHHOLD: | NDA | |
| pH: | NDA | |
| MELTING/FREEZING PT: | -40°F Max | |
| INITIAL BOILING POINT: @760° r | | |
| FLASH POINT: COC ^o F: | 293° | |
| EVAPORATION RATE (ETHYL ETHER = 1): <1 | | |
| FLAMMABILITY (solid, gas): | NA | |
| PERCENT VOLATILE (% BY VOL | .): 0 | |

UPPER/LOWER FLAM/EXP LMT: NDA VAPOR PRESSURE (mmHg): @ 100° F<0.1 VAPOR DENSITY (AIR = 1): 4 **RELATIVE DENSITY:** NDA SOLUBILITY IN WATER: NIL PART. COEF. N-OCT/H2O ≥5.7 **AUTOIGNITION TEMP:** NDA **DECOMPOSITION TEMP:** NDA SPECIFIC GRAVITY (H2O = 1): 0.88-.91 KINEMATIC VIS mm²/s @ 40°c 9.63

SECTION 10: STABILITY AND REACTIVITY

| STABILITY: | Stable |
|---|--|
| CONDITIONS CONTRIBUTING TO INSTABILITY: | None |
| INCOMPATIBILITY (MATERIAL TO AVOID): | May react with strong oxidizers. |
| HAZARDOUS DECOMPOSITION OR BY-PRODUC | TS: Normal combustion forms carbon dioxide and water vapor, |
| HAZARDOUS POLYMERIZATION: | and may produce oxides of sulfur and nitrogen. Incomplete combustion can produce carbon monoxide. Will not occur |

SECTION 11: TOXICOLOGICAL INFORMATION

| ACUTE STUDIES: HEALTH EFFECTS: CARCINOGENICITY: | Low order of acute oral or dermal toxicity Possible mild eye and skin irritant | | |
|---|---|--|--|
| | ACGIH, NTP, OSHA and IARC carcinogen lists were checked for those components with CAS Registry Numbers (64742-53-6). | | |
| ACGIH: IARC: | This product is not listed as carcinogenic. The International Agency for research on cancer has concluded that highly or severely refined light and middle distillates are Group 3 substances, "not classifiable as to their carcinogenicity to humans," based on inadequate human or animal evidence. | | |
| NTP: OSHA: | This product is not listed as carcinogenic. This product is not listed as carcinogenic. | | |

SECTION 12: ECOLOGICAL INFORMATION

| ECOTOXICITY: | No mortality or other adverse reactions to the exposures during or after |
|------------------------------|---|
| | 96 h. |
| PERSISTENCE & DEGRADABILITY: | Direct photolysis will not contribute to a measurable degradative removal of chemical components in this category from the environment. |
| BIOACCUMULATIVE POTENTIAL: | Inherently biodegradable |
| MOBILITY IN SOIL: | NDA |
| OTHER ADVERSE EFFECTS: | NDA |
| AQUATIC RELEASE: | Advise authorities if product has entered or may enter watercourses or sewer drains. |
| | |

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE RESIDUES DESCRIPTION:

SAFE HANDLING INFORMATION:

WASTE DISPOSAL METHOD:

This product is not a characteristic hazardous waste under RCRA. No EPA waste numbers are applicable for this product's components. See Section 7 (Handling and Storage) Observe Federal, State and Local regulations covering chemical waste spills.

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION:

PROPER SHIPPING NAME:

Not regulated as a hazardous material for transportation by USA DOT.

Listed

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

TSCA (TOXIC SUBSTANCE CONTROL ACT) REGISTRY:

CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION AND LIABILITY ACT): This product is not a hazardous substance under CERCLA.

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT):

302/304 This product is not listed as an extremely hazardous substance in 40 CFR Part 355, and is not known to contain an extremely hazardous substance in a concentration greater than one percent by weight.

| 311/312 HAZARD CATEGORIES: | Acute Health Hazard: | No |
|----------------------------|--------------------------|----|
| | Chronic Health Hazard: | No |
| | Fire Hazard: | No |
| | Pressure Release Hazard: | No |
| | Reactivity Hazard: | No |
| | | |

- **313** This product is not known to contain any components in concentrations above OSHA *de minimus* levels that are listed as toxic in 40 CFR Part 372 pursuant to the requirements of Section 313 of SARA.
- WHMIS: Listed

OSHA: 29 CFR 1910.1200 (Hazard Communication) required.

STATE REGULATIONS:

Distillate, Petroleum, Hydrotreated Light Naphthenic appears on the following state hazardous substances list.

MA

SECTION 16: OTHER INFORMATION

DATE REVISED: 11/06/19 SUPERCEDES: 8/20/18

The information provided in this Material Safety Data Sheet is believed to be accurate and reliable on and as of the date on this page. However, this Material Safety Data Sheet is not a guarantee or warranty of any kind, express or implied. Any and all warranties of merchantability and/or fitness for a particular purpose are specifically disclaimed. It is the user's responsibility to determine the conditions under which the product is used, including the selection of engineering controls, work practices and Personal Protective Equipment to minimize hazards.